CAX-BT01BM-2PS-28

Version 26.09

2MP Metal IP PoE Mini Bullet Camera
with Fixed Lens

Features:


- Adopts 2megapixel progressive CMOS, provides 2MP (1920×1080) @30FPS Stream
- 2.8mm/3.6mm fixed lens
- 2pcs of array LEDS, IR distance up to 30m
- PoE&DC12V
- DWDR, 3D DNR, AGC, MGC, AWB, ROI
- Real WDR 120dB
- IP67
- Smart Motion Detection
- Built-in Aipix Agent enables direct transmission of video, audio, and metadata to the video surveillance platform over a secure communication channel
- Traffic optimization through stream auto-pause on idle, preserving active RTSP connectivity



Powered by **Aipix Agent**

CAX-BT01BM-2PS-28

Dimensions:



Unit: mm (inch)

Specification:

Camera	**Solution**	SSC377 + SC231AH
	Image Sensor	1/3" 2Megapixel progressive scan CMOS
	Effective Pixels	3MP (2304 × 1280) / 2MP (1920 × 1080)
	Min. Illumination	0.01Lux @ (F1.8, AGC ON), 0 Lux with IR ON
	Shutter	1/2s – 1/50,000s
	Lens	2.8mm / 3.6mm fixed lens
	Day&Night	IR-CUT Auto Switch, Manual Switch, Timing Switch
	DNR	3D Digital Noise Reduction
	WDR	Yes, real WDR 120dB
Compression Standard	**Codec**	H.265+ / H.264+ / H.265 / H.264 / MJPEG
	Data Rate	Main: 256-8000kbps, Sub: 50-1000kbps
Image	**Max. Resolution**	3MP (2304 × 1280)
	Frame Rate	30fps @ 3MP / 2MP / 960P / 720P
	Main Stream	30fps 3MP (2304 × 1280) 30fps 2MP (1920 × 1080) 30fps 960P (1280 × 960) 30fps 720P (1280 × 720)
	Sub Stream	30fps D1 (704 × 576) 30fps VGA (640 × 480) 30fps HVGA (640 × 360) 30fps CIF (352 × 288)
	Features	DWDR, 3D DNR, AGC, MGC, AWB, ROI, Motion Detection, Privacy Masking
	Image Adjustment	Mirroring, Saturation, Brightness, Sharpness, Contrast Adjustment, Exposure, DWDR, Shutter, IRIS, LDC etc.
Network	**Protocols**	TCP/IP, UDP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP; SNMP v1/v2/v3, IPv4/v6; Bonjour; ICMP, IGMP, QoS, SSL/TLS
	Compatibility	HTTP CGI, ONVIF, WEBRTC

Network	**Private Protocols**	Support private protocols branded Hikvision, Dahua, Uniview, XM; Work plug and play with these NVRs and CMS; AI functions can work together with Uniview NVRs and CMS
	Detection	Smart Motion Detection
Interface	**Network**	RJ-45 LAN Port
	POE	Yes, Built-in
General	**Color**	White
	Accessories	Printed User Manual, Installation Kits
	Power Supply	PoE&DC12V
	Work Humidity	10% – 90%
	Operation Temperature	-40 to +60 °C
	Waterproof	Metal; IP67 waterproof; for indoor and outdoor
	Power Consumption	Max. 6W
	Size	152.1mm × 68.3mm × 62.9mm
	Weight	N.W.: 270g, G.W.: 350g

We reserve the right to change products and specifications without prior notice.
This information does not convey any license by any implication or otherwise under any patents or other rights.

WE MAKE LIFE SMARTER AND SAFER!

CONTACT AIPIX:

aipix.ai info@aipix.ai Jerozolemskie 85-21, Warszawa, 02-001, PL